

# TECHNICAL SPECIFICATIONS

## Marsh Buggy



### Carrier

Wetland 384-60-64-3c

### Build Date

2010

### Chassis:

I-Beam. Channel and tubing welded construction, bolted to pontoons, expanded metal decking with removable handrails. Buggy deck is full width and full length.

### Rig Dimensions

Base length (incl stairs):	11.75	m
Base width:	5.850	m
Height to Top of Canopy:	4.80	m
Height to Work Platform:	3.85	m
Weight:	35,000	kg

### Standard Features

Ground Pressure:	10.3	kpa
Speed Land:	3.0	km/hr
Speed Water:	1.0	km/hr

- Large pontoons for extra flotation.
- Disassembles into 4 pieces for transportation on 3 trailers.
- Three (3) rows of 10mm track chain gives stronger, longer chain and wear life and less ground pressure.

### Engine

John Deer 350hp, 6 cylinder, water cooled, turbo diesel.



### Pontoons

Recess tracks and UHMW pads keep mud and debris to a minimum. 9 Constructed compartments with four (4) being constructed for buoyancy.

### Hydraulic Drive System

Oversized heavy duty automatic. Two (2) speed hydraulic motor, brakes and planetary reducer with drive train and splined sprockets for final reduction.



Free call 1800 082 200  
[www.hagstromdrilling.com.au](http://www.hagstromdrilling.com.au)