

TECHNICAL SPECIFICATIONS

DR021 – LX6 Track Mounted Drill Rig



Carrier

Track Mounted

Build Date

2012

Rig Dimensions

Base length:	7.92	m
Base width:	2.60	m
Height Mast Up:	8.26	m
Weight:	6,500	kg

Standard Features

Usable Fuel Capacity:	60	l
Max Feed Force:	34	kN
Max Stroke:	4.00	m
Max Rod Pull:	6.00	m
Max Power:	53	kW
Max Torque:	6,540	Nm
Ground Pressure:	0.57	kg/cm ²

Maximum Practical Depth

NQ Drilling:	350	m
HQ Drilling:	273	m
HQ- Vwall Drilling:	346	m
PQ Drilling:	145	m

Recirculating Pump

Stalker:	50	SHL
Pump Flow (L/Min):	227	lpm
Max Pump Pressure:	450	psi

Water Pump

Main Pump:	FMC L0918	
Pump Flow (L/Min):	201	lpm
Max Pump Pressure:	600	psi



Features:

- Diesel power unit group Deutz D914L04 4.10
- liter 4 cylinder
- Hydraulic module
- Main winch c/w cable
- Hydraulic mast raising (independent)
- Lower mast assembly
- Levelling jacks (hydraulic)
- Rotary head
- Crawler - triple grouser type
- 12V Battery
- Foot Clamp and breaking cl



Free call 1800 082 200
www.hagstromdrilling.com.au