

TECHNICAL SPECIFICATIONS

DR012 – Hydra power Scout Mk V

Carrier

Hino 4x4 Truck Mounted

Build Date

August 2011

Rig Dimensions

Base length:	8.50	m
Base width:	2.50	m
Height Mast Down:	3.62	m
Height Mast Up:	9.36	m
Weight:	12,000	kg

Standard Features

Usable Fuel Capacity:	200	l
Max Feed Force:	43	kN
Max Stroke:	5.10	m
Max Rod Pull:	6.00	m
Max Power:	175	Kw
Max Torque:	2100	Nm
Ground Pressure:	0.36	kg/cm ²

Maximum Practical Depth

NQ Drilling:	365	m
HQ Drilling:	300	m
PQ Drilling:	165	m

Recirculating Pump

Stalker:	50	SHL
Pump Flow (L/Min):	227	lpm
Max Pump Pressure:	30	psi

Water Pump

Main Pump:	FMC W1122	
Pump Flow (L/Min):	140	lpm
Max Pump Pressure:	1000	psi



Features:

- Automatic Rotating Rod Guard
- Automatic Rod Loader
- Automatic Rotating Rod Guard
- Fire Extinguishers
- Emergency Shut Down System
- Hydraulic Rod Clamps
- Work Lights
- Safety Steps
- Lockable Battery Isolation Point
- Winch Limiter



Free call 1800 082 200
www.hagstromdrilling.com.au